

Delock PCI Express x1 Card to 2 x PS/2 and USB Pin Header - Low Profile Form Factor

Description

This PCI Express card by Delock expands the PC by **two PS/2 ports** and **one internal USB 2.0 pin header**. To the PS/2 ports different devices such as a keyboard and a mouse can be connected. The internal USB port can be used to connect USB devices, with the help of an optional cable.



Item no. 90049

EAN: 4043619900497 Country of origin: China

Package: Box

Specification

Connectors:

external:

2 x PS/2 female

internal:

1 x 9 pin USB 2.0 pin header male

1 x PCI Express x1, V1.0

1 x 4 pin power connector

- Chipset: ASIX MCS9990
- Data transfer rate up to:

Hi-Speed 480 Mbps,

Full-Speed 12 Mbps,

Low-Speed 1.5 Mbps

· Hot Plug, Plug & Play

System requirements

• Linux Kernel 5.4 or above

DATASHEET



- Windows 8.1/8.1-64/10/10-64/11
- Windows Server 2019
- PC with one free PCI Express slot

Package content

- PCI Express card
- · Low profile bracket
- User manual

Images











General

Supported operating system: Linux Kernel 5.4 or above

> Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows Server 2019

Interface

External: 2 x PS/2 female

Internal: 1 x 4 pin power connector

1 x 9 pin USB 2.0 pin header male

1 x PCI Express x1, V1.0a

Technical characteristics

Chipset: ASIX MCS9990