

PCI Express x16 Card to 1 x internal U.2 NVMe SFF-8639

Description

This PCI Express card by Delock expands the PC by one **U.2 interface**. It supports the connection of a U.2 SSD in 2.5" format. Further it is possible to connect a **2.5" SSD / HDD** by connecting the SATA port to the motherboard.

U.2
NVMe



Specification

- Connectors:
internal:
1 x U.2 SFF-8639 female
1 x PCI Express x16 (4-Lane), V4.0
1 x SATA 6 Gb/s 7 pin plug
- For 2.5" NVMe SSD or SATA HDD / SSD
- Bootable
- Supports NVM Express (NVMe)
- Supports TRIM
- 1 x LED indicator
- 4 x mounting hole for 2.5" drive

Item no. 90051

EAN: 4043619900510

Country of origin: China

Package: Retail Box



System requirements

- Linux Kernel 5.4 or above
- Windows 8.1/8.1-64/10/10-64
- Windows Server 2019
- PC with one free PCI Express x16 / x32 slot

Package content

- PCI Express card
- User manual

Images



General

Function:	bootable
Supported operating system:	Linux Kernel 5.4 or above Windows 10 32-bit Windows 10 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows Server 2019

LED indicator:	1 x
----------------	-----

Interface

Internal:	1 x U.2 SFF-8639 male 1 x SATA 7 pin plug 1 x PCI Express x4, V4.0
-----------	--