


Delock PCI Express x4 Card to 3 x USB Type-C™ + 2 x USB Type-A - SuperSpeed USB 10 Gbps - Low Profile Form Factor

Description

This PCI Express card by Delock expands the PC by **five USB 3.2 ports**. Different USB devices, such as docking stations, card readers, external enclosures etc., can be connected to the card.

Sufficient ports - 3 x USB Type-C™ and 2 x USB Type-A

The PCIe card offers three USB-C™ port as well as two USB Type-A ports. Thus devices can be connected with **10 Gbps** at each port.



Item no. 90060

EAN: 4043619900602

Country of origin: China

Package: Box

Specification

- Connectors:
external:
3 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female
1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) Type-A female
internal:
1 x PCI Express x4 (2-Lane), V3.0
1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) Type-A female
1 x SATA 15 pin power connector
- Chipset: Asmedia ASM3142, VIA VL822
- Data transfer rate up to:
SuperSpeed USB 10 Gbps,
SuperSpeed USB 5 Gbps,
Hi-Speed 480 Mbps,
Full-Speed 12 Mbps,
Low-Speed 1.5 Mbps
- Downwards compatible to USB 3.0, USB 2.0, USB 1.1
- Power supply via SATA power connector

- Electrical power:
USB Type-C™: max. 15 watt (5 V / 3 A)
USB Type-A: max. 4.5 watt (5 V / 0.9 A)
- Bootable
- Supports UASP
- Supports eXtensible Host Controller Interface (xHCI) specification 1.1
- Supports Multiple INs
- Operating temperature: 5 °C ~ 50 °C
- Storage temperature: -20 °C ~ 60 °C
- Humidity: 20 ~ 80 %

System requirements

- Linux Kernel 5.4 or above
- Windows 8.1/8.1-64/10/10-64
- Windows Server 2016
- PC with one free PCI Express x4 / x8 / x16 / x32 slot

Package content

- PCI Express card SuperSpeed USB 10 Gbps
- Low profile bracket
- User manual

Images



General

Function:	bootable
Supported operating system:	Linux Kernel 5.4 or above Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows Server 2016

Interface

External:	3 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female 1 x USB 10 Gbps Type-A female
Internal:	1 x PCI Express x4, V3.0 1 x SATA 15 pin power connector 1 x USB 10 Gbps Type-A female

Technical characteristics

Chipset:	Asmedia ASM3142 VIA VL822
Data transfer rate:	10 Gbps