

Delock PCI Express x4 Card to 1 x SuperSpeed USB 20 Gbps (USB 3.2 Gen 2x2) USB Type-C™ + 1 x USB Type-C™ PD 20 Watt

Description

This PCI Express card by Delock expands the PC by one external **USB 3.2** port. Different USB devices, such as docking stations, card readers, external enclosures etc., can be connected to the card.

SuperSpeed USB 20 Gbps

The card allows a data transfer rate of 20 Gbps on the USB-C™ port.

Power Delivery (PD) at the USB-C™ port

The USB Type-C™ port supports the Power Delivery function as well as diverse fast charging technologies. This allows connected devices such as smartphones, tablets and even laptops to be charged.



Item no. 90074

EAN: 4043619900749

Country of origin: China

Package: Retail Box

Specification

- Connectors:
external:
1 x SuperSpeed USB 20 Gbps (USB 3.2 Gen 2x2) USB Type-C™ female
1 x USB Type-C™ Power Delivery female
internal:
1 x PCI Express x4, V3.0
1 x SATA 15 pin power connector
- Chipset: Asmedia ASM3242
- Data transfer rate up to:
SuperSpeed USB 20 Gbps,
SuperSpeed USB 10 Gbps,
SuperSpeed USB 5 Gbps,
Hi-Speed 480 Mbps,
Full-Speed 12 Mbps,
Low-Speed 1.5 Mbps
- Downwards compatible to USB 3.0, USB 2.0, USB 1.1
- Electrical power data port: max. 15 watt (5 V / 3 A)

- Electrical power PD port: max. 20 watt (5 ~ 12 V)
- Bootable
- Supports UASP
- Supports eXtensible Host Controller Interface (xHCI) specification 1.1
- Supports Multiple INs

System requirements

- Linux Kernel 5.8 or above
- Windows 8.1/8.1-64/10/10-64
- PC with one free PCI Express x4 / x8 / x16 / x32 slot

Package content

- PCI Express card SuperSpeed USB 20 Gbps
- Low profile bracket
- User manual

Images



General

Form factor:	Low Profile
Function:	bootable
Supported operating system:	Linux Kernel 5.8.0 or above Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit

Interface

External:	1 x USB 20 Gbps USB Type-C™ female 1 x USB Type-C™ Power Delivery female
-----------	---

Technical characteristics

Chipset:	Asmedia ASM3242
Data transfer rate:	20 Gbps