


Delock PCI Express x8 Card to 2 x internal SFF-8643 NVMe - Low Profile Form Factor

Description

This PCI Express card by Delock expands the PC by **two SFF-8643** interfaces. SSD's with e.g. **U.2** interface can be connected to these ports by using an optional cable.



Item no. 90405

EAN: 4043619904051

Country of origin: China

Package: Box

Specification

- Connectors:
 - 2 x 36 pin SFF-8643 female
 - 1 x PCI Express x8, V3.0
- Chipset: Asmedia ASM2824
- Data transfer rate up to 32 Gbps
- Supports NVM Express (NVMe)
- Bootable
- 2 x LED indicator

System requirements

- Linux Kernel 4.6.4 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC with one free PCI Express x8 / x16 / x32 slot

Package content

- PCI Express card
- Low profile bracket
- User manual

Images



General

Form factor:	Low Profile
Function:	Bootable, ex UEFI 2.3.1
Supported operating system:	Linux Kernel 4.6.4 or above Windows 10 32-bit Windows 10 64-bit Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit
LED indicator:	2 x

Interface

Connector 1:	2 x 36 pin SFF-8643 female
Connector 2:	1 x PCI Express x8, V3.0

Technical characteristics

Chipset:	Asmedia ASM2824
Data transfer rate:	up to 32 Gbps

Physical characteristics

Slot bracket:	low profile standard
---------------	-------------------------