

Delock 3.5" USB 2.0 Card Reader 5 slot + 1 x USB 2.0 Type-A female

Description

This card reader by Delock can be installed into a **3.5" bay** of a PC and will be connected to an internal **USB 2.0 pin header male** port. It has a **five slot card reader** and enables the connection of one USB device.



Item no. 91708

EAN: 4043619917082 Country of origin: China Package: Retail Box

Specification

- Connectors: external:
 1 x CF slot
 1 x SD / MMC slot
 1 x ND slot
 1 x Micro SD slot
 1 x MS slot
 1 x USB 2.0 Type-A female internal:
 1 x 9 pin USB 2.0 pin header female
 Chipset: Realtek RTS5130
- Metal housing for installation into a 3.5" bay
- Data transfer rate up to 480 Mbps
- Bootable
- LED indicator for the card reader for power (red) and access (green)
- Cable data:
 - 1 x 9 pin USB 2.0 pin header female cable ca. 53 cm (incl. connector)
- Hot Swap, Plug & Play





• Supports following memory cards:

Slot 1

CF I, CF II, CF4.0, CF Ultra, CF Ultra DMA, CF Ultra II, CF Ultra III, CF Ultra IV, CF Extreme, CF Extreme III, CF Extreme IV, Microdrive, MagicStor

Slot 2

SD, SD Pro, SD Ultra, SD High Capacity (SDHC), Turbo-SD, SDHC Turbo, SD Ultra, SD Ultra II, SDHC Ultra, SDXC, SDXC Ultra, MMC-I, MMC-II, MMC plus, MMC plus Turbo, MMC 4.0, Mini SD*, Mini SDHC*, Turbo Mini SD*, MMCmobile*, RS-MMC*, RS-MMC 4.0*

Slot 3 xD, xD type M, xD type H

Slot 4 Micro SD, Micro SDHC, Micro SDHC Ultra, T-Flash, MMCmicro

Slot 5 MS Micro, MS-Pro Micro, MS-HG Micro, MS XC-HG Micro, M2 *Adapter is required

System requirements

- Linux Kernel 5.11 or above
- Windows 8.1/8.1-64/10/10-64/11
- PC with one free 3.5" bay
- Motherboard with a free 9 pin USB 2.0 pin header male

Package content

- 3.5" card reader with connection cable
- Screws
- User manual



Images





General

Function:	Hot Swap Plug & Play
Supported operating system:	Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows 11 Linux Kernel 5.11 or above
LED indicator:	2 x

Interface

External:	1 x CF slot 1 x MS slot 1 x Micro SD Slot 1 x SD slot 1 x xD slot 1 x USB 2.0 Type-A Buchse
Internal:	1 x 9 pin USB 2.0 pin header female

Technical characteristics

Chipset:	Realtek RTS5130
----------	-----------------

Physical characteristics

Cable length:
