

Delock 3.5" SuperSpeed USB Card Reader 6 slots + 1 x USB Type-A female

Description

This card reader by Delock can be installed into a free **3.5" bay** a PC and will be connected to a **USB pin header** port. It has **six different card reader slots** and enables the connection of one USB device.



Item no. 91759

EAN: 4043619917594 Country of origin: China Package: Retail Box

Specification

- Connectors:
 - external:
 - 1 x CF slot
 - 1 x SD slot
 - 1 x Micro SD slot
 - 1 x xD slot
 - 1 x MS slot
 - 1 x M2 slot
 - 1 x SuperSpeed USB 5 Gbps (USB 3.2 Gen 1) Type-A female internal:
 - 1 x 19 pin SuperSpeed USB (USB 3.2 Gen 1) pin header female
- Data transfer rate up to 5 Gbps
- 1 x LED indicator
- Metal housing for installation into a 3.5" bay
- Cable length: ca. 50 cm
- Hot Swap, Plug & Play
- Supports following memory cards:

Slot 1





CF I, CF II, CF4.0, CF Ultra, CF Ultra DMA, CF Ultra II, CF Ultra III, CF Ultra IV, CF Extreme, CF Extreme III, CF Extreme IV

Slot 2

SD, SD Pro, SD Ultra, SD High Capacity (SDHC), Turbo-SD, SDHC Turbo, SD Ultra, SD Ultra II, SDHC Ultra, SDXC, SDXC Ultra, MMC-I, MMC-II, MMC plus, MMC plus Turbo, MMC 4.0, Mini SD, Mini SDHC, Turbo Mini SD, MMCmobile, RS-MMC, RS-MMC 4.0

Slot 3

MicroSD, Micro SDHC, Micro SDXC

Slot 4

хD

Slot 5

MS, High Speed Memory Stick (HS-MS), MS Pro, MS Pro-HG, MS-HG, Memory Stick XC, MS Magic Gate, MS-Pro Magic Gate, MS-Duo, MS-Duo, MS-Duo, MS-Duo, MS-Duo, MS-Duo, MS-Duo, MS XC-Duo, MS XC-HG Duo

Slot 6

M2

System requirements

- Linux Kernel 5.8 or above
- Windows 8.1/8.1-64/10/10-64
- PC with one free 3.5" bay
- Motherboard with a free 19 pin SuperSpeed USB (USB 3.2 Gen 1) pin header male

Package content

- 3.5" card reader with connection cable
- Screws
- User manual



Images









General

Form factor:	3.5"
Function:	Hot Swap Plug & Play
Supported operating system:	Linux Kernel 5.8.0 or above Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit
LED indicator:	1 x

Interface

External:	1 x CF slot 1 x MS slot 1 x Micro SD Slot 1 x SD slot 1 x xD slot 1 x USB 5 Gbps Type-A female
Internal:	1 x USB 5 Gbps 19 pin pin header female 1 x M2 slot

Physical characteristics

|--|