

# Delock HD-SDI Outdoorcamera Bullet

## Description

This HD-SDI Surveillance Camera features a high-resolution 2 Megapixel sensor and delivers crystal-clear, uncompressed images with full HD resolution in real time. The HD-SDI output is compatible with other HD-SDI equipment. The signal is transmitted via a conventional 75 ohm coaxial cable with BNC connector, so an already existing infrastructure can be used. The built-in infrared LEDs and automatic day / night switching deliver detailed images even in the dark. The weatherproof enclosure is suitable for indoor and outdoor installation.



**Item no. 93235**

EAN: 4043619932351

Country of origin: China

Package: Box

## Specification

- Connector:
  - 1 x BNC female (HD-SDI: 1920 x 1080p with 25 or 30 Hz, SMPTE 292M)
  - 1 x BNC female (Composite Video: PAL or NTSC)
  - 1 x DC 5.5 x 2.1 mm Power (DC 12 V / 1.5 A)
- 2 Megapixel Progressive Scan CMOS Sensor (1 / 2.8")
- 2.8 - 12 mm zoom lens (manual)
- 72 integrated Infrared-LEDs, max. 60 m distance
- Internal cable routing (tamper protection)
- Water resistant enclosure with canopy
- Wired Joystick for OSD-control (optional controllable via RS-485)
- Picture Optimization: Automatic shutter control, automatic gain control (AGC), adaptive colour and contrast adaptation (ACCE), digital noise reduction (2D and 3D DNR), backlight compensation (BLC), automatic white balance (ATW), automatic day- / night switching
- Operating temperature: -10 ~ +50 °C
- Humidity: 0 ~ 85 % (non condensing)
- Dimensions (LxWxH): ca. 29 x 13 x 11 cm
- Weight: ca. 1.4 kg

## Specification of power connector

- Eingang: 12 V
- Masse außen, Plus innen
- Maße:
  - innen ø ca. 2,1 mm

außen: ø ca. 5,5 mm

Länge: ca. 9,5 mm

---

## System requirements

- Device with HD-SDI input or HD-SDI signal converter
  - Power supply with DC 12 V / 1.5 A (not included)
- 

## Package content

- HD-SDI Bullet Camera
  - Mounting screws and dowels
  - Allen wrench
  - User manual
- 

## Images

