

Delock Converter 3G-SDI to HDMI

Description

This Delock converter can be used to convert an HD- or 3G-SDI signal to an HDMI signal. You can connect e. g. a camera with HD-SDI output to an HDMI monitor. The SDI signal is transmitted via a conventional 75 Ohm coaxial cable with BNC connectors.



Item no. 93237

EAN: 4043619932375

Country of origin: China

Package: Box

Specification

- Connector:
 - Input:
 - 1 x BNC female (SDI)
 - Output:
 - 1 x BNC female (SDI, pass-through)
 - 1 x HDMI-A female
- Chipset: GV7601
- Supports 3G-SDI Level A
- Supported resolution:
 - SD 480i, 525i and 625i
 - HD 720p 24, 25, 30, 50 and 60 Hz
 - HD 1080i 50, 60 Hz
 - HD 1080p 24, 25, 30, 50 and 60 Hz
- Supported data rate: 270 Mb/s ~ 2.97 Gb/s
- Supports 8 channels of 48 kHz PCM audio
- Robust metal housing
- Power consumption: max. 2.5 W
- Dimensions (LxWxH): ca. 100 x 70 x 25 mm


Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.3 A
- Output: 5 V / 1 A
- Ground outside, plus inside
- Dimensions:
inside: ø ca. 2.1 mm
outside: ø ca. 5.5 mm
length: ca. 9 mm

Package content

- 3G-SDI > HDMI Converter
- Mounting brackets and screws
- Power supply

Images



Interface

Connector 1:	1 x BNC female
Connector 2:	1 x HDMI-A female
connector 3:	1 x BNC female

Technical characteristics

Chipset:	GV7601
----------	--------

Physical characteristics

Length:	100 mm
Width:	70 mm
Height:	25 mm