

# Delock USB 2.0 Camera Module 5 mega pixel IMX179QQH5-C Sony® Starvis<sup>™</sup> 64° V51 auto focus

### Description

This USB 2.0 camera module by Delock offers in a compact construction a high resolution and low power consumption. It is ideally suited for installation in industrial components like IPCs, embedded systems, sensors and in device manufacture. The use of a photosensitive sensor with back side illumination (BSI) expands the scope of this module.

#### Note

The auto focus of this camera module can be deactivated and adjusted individually.



#### Item no. 96361

EAN: 4043619963614 Country of origin: China Package: Retail Box

### Specification

- Connector: 1 x 5 pin USB 2.0 pin header female SMT, pitch 1.00 mm
- Resolution: 5.0 megapixel
- With optical IR filter
- Current consumption: sensor active: 110 mA ± 5 mA @ 640 x 480 pixel
- Operating voltage: 5 V DC
- Operating temperature: 5 °C ~ 50 °C
- Operating humidity: 20 ~ 80 %
- Sensor size: 1/3.2"
- Sensitivity: 0.6 V / Ix s
- Signal-to-noise ratio (SNR): ca. 36 dB
- Dynamic range: 68 dB
- Auto focus: 0.2 m infinite
- Aperture: F/2.8
- Frame rates:

320 x 240 @ 30 Hz 352 x 288 @ 30 Hz 640 x 480 @ 30 Hz 900 x 600 @ 30 Hz 1280 x 720 @ 30 Hz

#### **DATASHEET**



- 1600 x 1200 @ 30 Hz
- 1920 x 1080 @ 30 Hz
- 2048 x 1536 @ 20 Hz
- 2560 x 1440 @ 30 Hz
- 2592 x 1944 @ 20 Hz
- Dimensions (LxWxH): ca. 60.0 x 9.0 x 5.8 mm

### System requirements

- Android 11.0 or above
- Chrome OS
- Linux Kernel 5.15 or above
- Mac OS 12.4 or above
- Windows 10/10-64/11

### Package content

- Camera Module
- CD with user manual

### Images







### General

| Supported operating system: | Chrome OS                  |
|-----------------------------|----------------------------|
|                             | Windows 11                 |
|                             | Mac OS 12.4 oder höher     |
|                             | Android 11.0 or above      |
|                             | Linux Kernel 5.15 or above |

### Interface

| connector: | 1 x 5 pin USB 2.0 WTB female |
|------------|------------------------------|
|            |                              |

### **Technical characteristics**

| Operating voltage:         | 5 V DC                          |
|----------------------------|---------------------------------|
| Operating temperature:     | 5 °C ~ 50 °C                    |
| Maximum screen resolution: | 2592 x 1944 @ 20 fps            |
| Minimum screen resolution: | 320 x 240 @ 30 fps              |
| Sensor Size:               | 1/3.2"                          |
| Current consumption:       | 110 mA ± 5 mA @ 640 x 480 Pixel |

## **Physical characteristics**

| Length: | 60.0 mm |
|---------|---------|
| Width:  | 9.0 mm  |
| Height: | 5.8 mm  |